ENGINE CRANES

- Heavy duty welded construction with rugged reinforced tubular steel
- Metered control release valve for lowering boom at a precisely controlled rate of speed
- Special 8 ton hydraulic crane jacks are equipped with a built-in by-pass mechanism, U.S. patent No.5,946,912



44010 Folded position

44010
1 Ton Capacity
Folding Design

44020
2 Ton Capacity

Model	Boom Capacity @ Length	Hook Height		Base Length	Front Base Width	Rear Base Width	Height	Wheel Diameter		G.W.
		Min.	Max.					Front	Rear	
44010	1 Ton	4-7/8″	82-1/4″	71-5/8″	18-1/2″~44-7/8″	31-1/2″	65″	5″	3-1/2″	250 Lbs.
	3/4 Ton	3-3/8″	85″							
	1/2 Ton	-	86-5/8″							
44020	2 Ton	18-3/8″	69-1/4″	62-1/2″	29″~33-7/8″	34-5/8″~53-1/8″	57″	3-1/2″		264 Lbs.
	1-1/2 Ton	14″	75-1/4″	71-1/2″						
	1 Ton	9-1/4″	81-1/4″	80-1/2″						
	1/2 Ton	5″	86-1/2″	89-1/2″						

CRANE JACKS

Crane jacks have internal load-limiting device to protect crane and user from overload.

- Hydraulic system is protected from internal damage by a patented by-pass mechanism, U.S. Patent No.5,946,912
- Machined and polished cylinders with die-cut threads provide non-abrasive leak-free, durable performance
- Fabricated from hard-cast steel with heat-treated critical stress areas
- A wide, rugged base provides stability and strength



44980
8 Ton Capacity



44940
4 Ton Capacity

Model	Capacity	Minimum Height	Maximum Height	Base Size	G.W.
44915	1-1/2 Ton	19-7/8″	35-1/4″	5-18″ X 4-1/2″	17 Lbs.
44930	3 Ton				
44940	4 Ton				
44980	8 Ton	24-1/8″	43-1/4″	5″ X 4-3/4″	31 Lbs.
44981 Air				7-1/8″ X 5″	38 Lbs.